### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Revision date: 2/11/2019 Supersedes: 9/7/2018 Version: 8.1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance

Name : Trizinc Dicitrate Dihydrate
Trade name : ZINC CITRATE (DIHYDRATE)

EC-No. : 208-901-2 CAS-No. : 5990-32-9

REACH registration No

Formula :  $Zn_3(C_6H_5O_7)_2 \cdot 2H_2O$ 

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Use of the substance/mixture : Pharmaceutical industry

Food-stuff industry Ink for offset printing

#### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

#### Distributor

Chanjao Longevity Co., Ltd. 50 Ramindra 14, Bangkok 10230 THAILAND

+66 2 002 7 002

care@myskinrecipes.com

#### 1.4. Emergency telephone number

Emergency number : For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or

Accident +66 2 002 7 002

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Irrit. 2 H319
Aquatic Acute 1 H400
Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

#### Adverse physicochemical, human health and environmental effects

Causes serious eye irritation. Very toxic to aquatic life with long lasting effects. Not classified as flammable according to EC criteria, but may present a risk in the event of a fire.

#### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS07

GHS09

Signal word (CLP) : Warning

Hazard statements (CLP) : H319 - Causes serious eye irritation.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP) : P273 - Avoid release to the environment.

P280 - Wear eye protection, face protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P391 - Collect spillage.

P501 - Dispose of contents/container to an approved waste disposal plant.

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Name	Product identifier		Classification according to Regulation (EC) No. 1272/2008 [CLP]
INCI: Zinc Citrate	(CAS-No.) 5990-32-9 (EC-No.) 208-901-2	99 - 100	Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

#### 3.2. Mixtures

Not applicable

#### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

: Move the affected person away from the contaminated area and into the fresh air. Get First-aid measures after inhalation

medical advice and attention if you feel unwell.

First-aid measures after skin contact : Wash with soapy water. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Consult an

ophthalmologist if irritation persists.

First-aid measures after ingestion : Drink plenty of water as a precaution. Get medical advice and attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Metal fume fever. Symptoms/effects after eye contact : Eye irritation

Symptoms/effects after ingestion : Nausea. Vomiting. Diarrhea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Carbon dioxide. Dry powder. Foam.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : On combustion or on thermal decomposition (pyrolysis) releases : Carbon oxides (CO,

CO2). Zinc oxide.

#### 5.3. Advice for firefighters

: Contain the extinguishing fluids by bunding (the product is hazardous for the environment). Firefighting instructions

Use water spray or fog for cooling exposed containers.

: Do not attempt to take action without suitable protective equipment. Complete protective Protection during firefighting

clothing. Self-contained breathing apparatus.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

**Emergency procedures** : Avoid contact with skin and eyes. Do not breathe dust.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Do not allow product to spread into the environment. Do not discharge into drains or rivers.

#### 6.3. Methods and material for containment and cleaning up

: Sweep up or vacuum up the product. Collect up the product and place it in a spare For containment

container suitably labelled.

Methods for cleaning up : Dispose of contaminated materials in accordance with current regulations.

#### 6.4. Reference to other sections

For further information refer to section 13.

2/11/2019 (Version: 8.1) 2/16 EN (English)

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Extraction to remove dust at its source. Avoid

contact with skin and eyes. Avoid creating or spreading dust.

Hygiene measures : Do not drink, eat or smoke in the workplace. Always wash hands after handling the

product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Take all necessary measures to avoid accidental discharge of products into drains and

waterways due to the rupture of containers or transfer systems.

Storage conditions : Store in dry, cool, well-ventilated area. Keep container tightly closed. Protect from

moisture.

Incompatible materials : Strong oxidizing agents.

Packaging materials : Plastic materials. Polyethylene.

7.3. Specific end use(s)

No additional information available

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Frizinc Dicitrate Dihydrate (5990-32-9)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal	3.57 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.25 mg/m³
PNEC (Water)	
PNEC aqua (freshwater)	7.8 μg/l
PNEC aqua (marine water)	2 μg/l
PNEC (Sediment)	
PNEC sediment (freshwater)	11 mg/kg
PNEC sediment (marine water)	1.1 mg/kg
PNEC (Soil)	
PNEC soil	23 mg/kg
PNEC (STP)	

## PNEC sewage treatment plant 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station. Extraction to remove dust at its source.

52 μg/l

#### Hand protection:

Protective gloves. The protective gloves to be used must comply with the specifications of EC directive 89/686/EEC and the resultant standard EN 374. Breakthrough time: refer to the recommendations of the supplier

#### Eye protection:

Safety glasses

#### Respiratory protection:

If dust are formed: Gas mask with filter type P1/FFP1

#### **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Physical state: SolidAppearance: Powder.Molecular mass: 610.36 g/molColour: White to off-white.Odour: Sweetish.

Odour threshold : No data available pH : Not applicable Relative evaporation rate (butylacetate=1) : No data available

2/11/2019 (Version: 8.1) EN (English) 3/16

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Melting point : 295 °C (Decomposes)

Freezing point : Not applicable

Boiling point : Not applicable

Flash point : Not applicable

Auto-ignition temperature : No data available

Decomposition temperature : 165 °C

Flammability (solid, gas) : No data available

Vapour pressure : Insignificant (Results obtained on a similar product)

Relative vapour density at 20 °C : No data available

Relative density : 1.7 (≥ 2) (20 °C) (results obtained by read-across)

Solubility : Water: Slighlty soluble
Log Pow : No data available
Log Kow : -0.2 - -1.8 (Citric acid)
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : Not explosive.

Oxidising properties : Non oxidizing material according to EC criteria.

Explosive limits : No data available

#### 9.2. Other information

No additional information available

#### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

To our knowledge, the product does not present any particular risk, under normal conditions of use.

#### 10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

#### 10.3. Possibility of hazardous reactions

None to our knowledge.

#### 10.4. Conditions to avoid

None to our knowledge.

## 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

#### **SECTION 11: Toxicological information**

11.1. Information on toxicological effects	
Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Trizinc Dicitrate Dihydrate (5990-32-9)	)
LD50 oral rat	> 2000 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg (Results obtained on a similar product) (OECD 402 method)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
	pH: Not applicable
Additional information	: (Results obtained on a similar product) (OECD 404 method)
Serious eye damage/irritation	: Causes serious eye irritation.
	pH: Not applicable
Additional information	: EpiOcular (OECD 492 method)
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (Results obtained on a similar product) (OECD 406 method)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (Results obtained on a similar product) (OECD 471 method)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Additional information	: (Results obtained on a similar product)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Additional information : (Results obtained on a similar product)
(OECD 416 method)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Additional information : (Results obtained on a similar product)

(OECD 408 method)

#### Trizinc Dicitrate Dihydrate (5990-32-9)

NOAEL (oral, rat, 90 days) 234 mg/kg bodyweight/day (male)

Aspiration hazard : Not classified (Technical impossibility to obtain the data)

#### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

# Trizinc Dicitrate Dihydrate (5990-32-9) LC50 fish 0.4 mg/l/96h (Leuciscus idus) (Results obtained on a similar product) EC50 Daphnia 0.2 mg/l/48 h (Daphnia magna) (Results obtained on a similar product) NOEC chronic algae 0.015 mg/l/72 h (P. subcapitata) (Results obtained on a similar product)

#### 12.2. Persistence and degradability

#### **Trizinc Dicitrate Dihydrate (5990-32-9)**

Persistence and degradability Readily biodegradable. 97 % biodegradation. (28 days). (OECD 301B method). (Results obtained on a similar product).

#### 12.3. Bioaccumulative potential

#### Trizinc Dicitrate Dihydrate (5990-32-9)

Log Kow -0.2 - -1.8 (Citric acid)

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

#### Trizinc Dicitrate Dihydrate (5990-32-9)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Other adverse effects

No additional information available

#### **SECTION** 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of in accordance with relevant local regulations.

Product/Packaging disposal recommendations : Destroy at an authorised site. Discharging into rivers and drains is forbidden.

Additional information : Empty the packaging completely prior to disposal. Recycle or dispose of in compliance with current legislation.


#### **SECTION 14: Transport information**

In accordance with ADR / IATA / IMDG

in decidate many bry many impe		
ADR	IMDG	IATA
14.1. UN number		
UN 3077	UN 3077	UN 3077
14.2. UN proper shipping name		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc citrate)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Zinc citrate)	Environmentally hazardous substance, solid, n.o.s. (Zinc citrate)
14.3. Transport hazard class(es)		
9	9	9

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830



#### 14.6. Special precautions for user

#### **Overland transport**

Classification code (ADR) : M7

Special provisions (ADR) : 274, 335, 601, 375

Limited quantities (ADR) : 5kg Excepted quantities (ADR) : E1

Packing instructions (ADR) : P002, IBC08, LP02, R001

Mixed packing provisions (ADR) : MP10 Portable tank and bulk container instructions : T1, BK1, BK2

(ADR)

Portable tank and bulk container special provisions : TP33

(ADR)

Tank code (ADR) : SGAV, LGBV

Vehicle for tank carriage : AT Transport category (ADR) : 3 Special provisions for carriage - Packages (ADR) : V13 Special provisions for carriage - Bulk (ADR) : VC1, VC2 Special provisions for carriage - Loading, : CV13

unloading and handling (ADR)

: 90 Hazard identification number (Kemler No.)

Orange plates

90 3077

Tunnel restriction code (ADR) : E EAC code : 2Z

#### Transport by sea

: 274, 335, 966, 967, 969 Special provisions (IMDG)

Limited quantities (IMDG) : 5 kg : E1 Excepted quantities (IMDG)

Packing instructions (IMDG) : P002, LP02 : PP12 Special packing provisions (IMDG) IBC packing instructions (IMDG) : IBC08 IBC special provisions (IMDG) : B3

: T1, BK1, BK2, BK3 Tank instructions (IMDG)

: TP33 Tank special provisions (IMDG) EmS-No. (Fire) : F-A EmS-No. (Spillage) : S-F Stowage category (IMDG) : A Stowage and handling (IMDG) : SW23 MFAG-No : 171

#### Air transport

PCA Excepted quantities (IATA) : E1 PCA Limited quantities (IATA) : Y956 PCA limited quantity max net quantity (IATA) : 30kgG PCA packing instructions (IATA) : 956 PCA max net quantity (IATA) : 400kg CAO packing instructions (IATA) : 956

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

CAO max net quantity (IATA) : 400kg

Special provisions (IATA) : A97, A158, A179, A197

ERG code (IATA) : 9L

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

#### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

#### No REACH Annex XVII restrictions

Trizinc Dicitrate Dihydrate is not on the REACH Candidate List

Trizinc Dicitrate Dihydrate is not on the REACH Annex XIV List

Trizinc Dicitrate Dihydrate is not subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Trizinc Dicitrate Dihydrate is not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC

#### 15.1.2. National regulations

No additional information available

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has been carried out

#### **SECTION 16: Other information**

#### Indication of changes:

This sheet was updated (refer to the date at the top of this page). SDS changed sections: 14.

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

2/11/2019 (Version: 8.1) EN (English) 7/16

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### ANNEX TO THE SAFETY DATA SHEET

Identified Uses	Es N°	Short title	Page
Formulation of preparations	1		8
Consumer use	2		15

#### 1. 1: Formulation of preparations

#### 1.1. Title section

## Formulation of preparations

ES Ref.: 1 Date of issue: 01/07/2013 ES Type: Worker Version: 2.0 Revision date: 10/09/2018

Environment		
	Contributing scenario controlling environmental exposure	ERC2
	Contributing scenario controlling environmental exposure	ERC3
Worker		
	Worker Contributing Scenario	PROC2
	Worker Contributing Scenario	PROC3
	Worker Contributing Scenario	PROC4
	Worker Contributing Scenario	PROC4
	Worker Contributing Scenario	PROC5
	Worker Contributing Scenario	PROC5
	Worker Contributing Scenario	PROC8a
	Worker Contributing Scenario	PROC8b
	Worker Contributing Scenario	PROC9

Processes, tasks, activities covered

#### 1.2. Conditions of use affecting exposure

#### 1.2.1. Control of environmental exposure: Contributing scenario controlling environmental exposure (ERC2)

ERC2 Formulation into mixture

#### Product (article) characteristics

Physical form of product	Powder
Volatility	Low volatility

#### Amount used, frequency and duration of use (or from service life)

Maximum daily site tonnage (kg/d):	(Zn) 140
Annual site tonnage (tons/year):	(Zn) 42

#### Technical and organisational conditions and measures

Removal of solids in settling tanks

#### Conditions and measures related to sewage treatment plant

Size of the STP: 2000 m³/day (by default)

#### Conditions and measures related to treatment of waste (including article waste)

Reprocess or burn in an approved incinerator	
Controlled application to agricultural soil	

#### 1.2.2. Control of environmental exposure: Contributing scenario controlling environmental exposure (ERC3)

ERC3	Formulation into solid matrix
Product (article) character	istics

Physical form of product	Powder
Volatility	Low volatility

#### Amount used, frequency and duration of use (or from service life)

Maximum daily site tonnage (kg/d):	(Zn) 140
Annual site tonnage (tons/year):	(Zn) 42

2/11/2019 (Version: 8.1) EN (English) 8/16

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (EC) No. 1907/2006 (REACH) with its am	endment Regulation (EU) 2015/830					
Technical and organisational conditions and measur	res					
Removal of solids in settling tanks						
Conditions and measures related to sewage treatment plant						
Size of the STP: 2000 m³/day (by default)	Size of the STP: 2000 m³/day (by default)					
Conditions and measures related to treatment of was	ste (including article waste)					
Reprocess or burn in an approved incinerator						
Controlled application to agricultural soil						
1.2.3. Control of worker exposure: Worker Contributin	1.2.3. Control of worker exposure: Worker Contributing Scenario (PROC2)					
· · · · · · · · · · · · · · · · · · ·	process with occasional controlled expo	sure				
Product (article) characteristics						
Physical form of product						
Dustiness	Solid, high dustiness					
Amount used (or contained in articles), frequency an	d duration of use/exposure					
Exposure duration	> 4 h/day					
1 time a day						
Technical and organisational conditions and measur	205					
Local exhaust ventilation - efficiency of at least		90				
Handle in accordance with good industrial hygiene and s	afety practice					
Avoid raising powdered material due to explosion hazard charge	I,Prevent the build-up of electrostatic					
Conditions and measures related to personal protect	tion, hygiene and health evaluation					
Impermeable protective gloves. Safety glasses. Protective	ve clothing					
Other conditions affecting workers exposure						
Exposed skin surface (cm²): 480 (two hands, face side of	only)					
Respiration volume	10 m³					
1.2.4. Control of worker exposure: Worker Contributin	g Scenario (PROC3)					
	ss (synthesis or formulation)					
Product (article) characteristics						
Physical form of product	Powder					
Dustiness	Solid, high dustiness					
Amount used (or contained in articles), frequency an						
Exposure duration	> 4 h/day					
1 time a day	- 1.17day					
•						
Technical and organisational conditions and measur  Local exhaust ventilation - efficiency of at least	es	90				
Handle in accordance with good industrial hygiene and s	afety practice	00				
Avoid raising powdered material due to explosion hazard charge	I,Prevent the build-up of electrostatic					
Conditions and measures related to personal protect	tion, hygiene and health evaluation					
· · · · · · · · · · · · · · · · · · ·	Impermeable protective gloves. Safety glasses. Protective clothing					
Other conditions affecting workers exposure						
Exposed skin surface (cm²): 240 (one hand, face side on						
Respiration volume	10 m³					
1.2.5. Control of worker exposure: Worker Contributing Scenario (PROC4)						
PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises						
Product (article) characteristics						
Physical form of product Powder						
Dustiness Solid, high dustiness						
Amount used (or contained in articles), frequency and duration of use/exposure						
Amount used (or contained in articles), frequency an Exposure duration  1 time a day	d duration of use/exposure  1-4 h/day					

2/11/2019 (Version: 8.1) EN (English) 9/16

Dustiness

Technical and organisation	nal conditions and measur	endment Regulation (EU) 2015/830		
Local exhaust ventilation - e			90	
	ndle in accordance with good industrial hygiene and safety practice			
Avoid raising powdered mat charge	erial due to explosion hazard	I,Prevent the build-up of electrostatic		
		tion, hygiene and health evaluation		
Impermeable protective glov	ves. Safety glasses. Protectiv	ve clothing		
Other conditions affecting	workers exposure			
Exposed skin surface (cm²)	: 480 (two hands, face side of	only)		
Respiration volume			10 m³	
.2.6. Control of worker exp	osure: Worker Contributin	g Scenario (PROC4)		
PROC4	Use in batch and other pro	ocess (synthesis) where opportunity for	exposure arises	
Product (article) character	ristics			
Physical form of product		Powder		
Dustiness Solid, high dustiness				
Amount used (or contained	ed in articles), frequency an	d duration of use/exposure		
Exposure duration		15min- 1 h/day		
1 time a day				
Technical and organisation	nal conditions and measur			
Local exhaust ventilation - e			90	
	good industrial hygiene and s	afety practice		
Avoid raising powdered material due to explosion hazard, Prevent the build-up of electrostatic charge				
Conditions and measures	related to personal protect	tion, hygiene and health evaluation		<u> </u>
Impermeable protective glov	ves. Safety glasses. Protectiv	ve clothing		
Other conditions affecting	ı workers exposure		•	
	: 480 (two hands, face side of	only)		
Respiration volume		•	10 m³	
2.7. Control of worker exp	oosure: Worker Contributin	g Scenario (PROC5)		
PROC5		n processes for formulation of preparation	ons and articles (	multistage and/or significant
Product (article) character	ristics			
Physical form of product		Powder, Solid in solution		
Dustiness		Solid, high dustiness, Solid, low dustin	ness	
Amount used (or containe	ed in articles) frequency an	d duration of use/exposure		
Exposure duration	a in artiology, frequency an	1-4 h/day		
1 time a day				
<u> </u>	nal conditions and measur			
Local exhaust ventilation - e		65	90	
	good industrial hygiene and s	afety practice	90	
Avoid raising powdered mat charge	erial due to explosion hazard	I,Prevent the build-up of electrostatic		
Conditions and measures	related to personal protect	tion, hygiene and health evaluation		•
	ves. Safety glasses. Protectiv			
Other conditions affecting				
	: 480 (two hands, face side of	only)		
Respiration volume		·····//	10 m³	
· · · · · · · · · · · · · · · · · · ·	occure: Worker Cantribution	a Sconario (BBOCE)	1	
PROC5	Mixing or blending in batch contact)	n processes for formulation of preparation	ons and articles (	multistage and/or significant
	contact)			
Product (article) character Physical form of product	ristics	Powder, Solid in solution		

2/11/2019 (Version: 8.1) EN (English) 10/16

Solid, high dustiness, Solid, low dustiness

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

according to Regulation (LC) No.	1907/2000 (INEACT) WITH Its affic	endinent Regulation (LO) 2013/030					
Amount used (or containe	d in articles), frequency an	d duration of use/exposure					
Exposure duration		15min- 1 h/day					
1 time a day							
Technical and organisational conditions and measures							
Local exhaust ventilation - e			90				
	good industrial hygiene and s	afety practice					
Avoid raising powdered mate charge	erial due to explosion hazard	I,Prevent the build-up of electrostatic					
Conditions and measures	related to personal protect	tion, hygiene and health evaluation					
Impermeable protective glov	es. Safety glasses. Protectiv	re clothing					
Other conditions affecting	workers exposure		l .				
Exposed skin surface (cm²)		only)					
Respiration volume		,,	10 m³				
1.2.9. Control of worker exp	osure: Worker Contributin	g Scenario (PROC8a)					
PROC8a		reparation (charging/discharging) from/to	o vessels/large o	containers at non dedicated			
Product (article) character	istics						
Physical form of product	151105	Powder					
Dustiness		Solid, high dustiness					
	d in articles), frequency an	d duration of use/exposure					
Exposure duration		15min- 1 h/day					
1 time a day							
Technical and organisation		es					
Local exhaust ventilation - et		afoty practice	90				
-	good industrial hygiene and s	I,Prevent the build-up of electrostatic		Γ			
charge							
		tion, hygiene and health evaluation	1				
Impermeable protective glov	es. Safety glasses. Protectiv	ve clothing					
Other conditions affecting	workers exposure						
Exposed skin surface (cm²)	: 960 (two hands)						
Respiration volume			10 m³				
1.2.10. Control of worker ex	posure: Worker Contributi	ng Scenario (PROC8b)					
PROC8b	Transfer of substance or p	reparation (charging/discharging) from/to	o vessels/large o	containers at dedicated facilities			
Product (article) character	istics						
Physical form of product		Powder					
Dustiness		Solid, high dustiness					
Amount used (or containe	d in articles), frequency an	d duration of use/exposure					
Exposure duration	, <b>-</b>	15min- 1 h/day					
1 time a day		,					
Technical and organisational conditions and measures  Local exhaust ventilation - efficiency of at least  90							
Handle in accordance with good industrial hygiene and safety practice							
Avoid raising powdered material due to explosion hazard, Prevent the build-up of electrostatic charge							
Conditions and measures related to personal protection, hygiene and health evaluation							
Impermeable protective glov							
Other conditions affecting workers exposure  Exposed skin surface (cm²): 480 (two hands, face side only)							
Respiration volume	. +00 (two nands, lace side o	n ny j	10 m <sup>3</sup>				
·			10111-				
1.2.11. Control of worker ex		<u> </u>	9p p +				
PROC0	I Transfer of substance or m	nixture into small containers (dedicated f	uuna una includi	ina welahina)			

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its am	endment Regulation (EU) 2015/830		
Product (article) characteristics			
Physical form of product	Powder		
Dustiness	Solid, high dustiness		
Amount used (or contained in articles), frequency ar	nd duration of use/exposure		
Exposure duration	15min- 1 h/day		
1 time a day			
Technical and organisational conditions and measur	res		
Local exhaust ventilation - efficiency of at least		90	
Handle in accordance with good industrial hygiene and safety practice			
Avoid raising powdered material due to explosion hazard, Prevent the build-up of electrostatic charge			
Conditions and measures related to personal protect	tion, hygiene and health evaluation		·
Impermeable protective gloves. Safety glasses. Protective	ve clothing		
Other conditions affecting workers exposure			
Exposed skin surface (cm²): 480 (two hands, face side only)			
Respiration volume			
1.3. Exposure estimation and reference to i	ts source		
1.2.1 Environmental release and exposure Contributi		-L (ED	20)

#### 1.3.1. Environmental release and exposure Contributing scenario controlling environmental exposure (ERC2)

Release route			Release rate		Release estimation method		
Release fraction to wastew	vater		0.02	.02 (ERC 2)			
Release fraction to wastew	vater		0.0009 (TGD II,2,A)		A)		
Release fraction to air from	n process		0.00002			(TGD II,2,A	A)
Release fraction to air from process			0.0002		(TGD IV,2,A)		
Protection target	Unit	Exposure estimation		PNEC	RCF	ł	Assessment method
Freshwater	μg/l	0.217		7.8	0.02	8	EUSES
Marine water	μg/l	0.0264		2	0.01	3	EUSES

Freshwater sediment	mg/kg	5.19	11	0.472	EUSES
Marine water sediment	mg/kg	0.632	1.1	0.575	EUSES
Sewage treatment plant	μg/l	3.5	52	0.067	EUSES
Soil	mg/kg	1.15	23	0.05	EUSES

## 1.3.2. Environmental release and exposure Contributing scenario controlling environmental exposure (ERC3)

Release route		Release rate		Release estimation method			
Release fraction to wastewater			0.002		(ERC 3)		
Release fraction to wastew	ewater 0.02			(TGD II,2.1,A)			
Release fraction to air from	process	process 0.3 (ERC 3)		0.3			
Release fraction to air from process		0.001		(TGD II,2.1,A)			
Protection target	Unit	Fynosi	Iro	DNEC	DCE		Assassment method

Troicase fraction to all from	i piocess		0.001			(100 11,2.1,74)		
Protection target	Unit	Exposu estimat		PNEC	RCF	}	Assessment method	
Freshwater	μg/l	0.217		7.8	0.02	8	EUSES	
Marine water	μg/l	0.0264		2	0.01	3	EUSES	
Freshwater sediment	mg/kg	5.19		11	0.47	2	EUSES	
Marine water sediment	mg/kg	0.632		1.1	0.57	5	EUSES	
Sewage treatment plant	μg/l	3.5		52	0.06	7	EUSES	
Soil	mg/kg	1.15		23	0.05		EUSES	

## 1.3.3. Worker exposure Worker Contributing Scenario (PROC2)

Route of exposure and type of effects	Exposure estimate	RCR	Method
Inhalation - Long-term - systemic effects	0.1 mg/m³	0.08	ECETOC TRA worker
Sum RCR - Long-term - systemic effects		0.08	

#### 1.3.4. Worker exposure Worker Contributing Scenario (PROC3)

Route of exposure and type of effects	Exposure estimate	RCR	Method
Inhalation - Long-term - systemic effects	0.1 mg/m³	0.08	ECETOC TRA worker
Sum RCR - Long-term -		0.08	

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

systemic effects		
1.3.5. Worker exposure Worker (	Contributing Scenario (PROC4)	

Route of exposure and type of effects	Exposure estimate	RCR	Method
Inhalation - Long-term - systemic effects	1.5 mg/m³	1.2	ECETOC TRA worker
Sum RCR - Long-term - systemic effects		1.2	

#### 1.3.6. Worker exposure Worker Contributing Scenario (PROC4)

Route of exposure and type of effects	Exposure estimate	RCR	Method
Inhalation - Long-term - systemic effects	0.5 mg/m <sup>3</sup>	0.4	ECETOC TRA worker
Sum RCR - Long-term -		0.4	
systemic effects			

#### 1.3.7. Worker exposure Worker Contributing Scenario (PROC5)

#### Information for contributing exposure scenario

Dermal uptake of solid citrates is expected to be negligible and is not considered, Dermal uptake factor of 0.02 applied for the liquid formulation

Route of exposure and type of effects	Exposure estimate	RCR	Method
Dermal - Long-term - systemic effects	0.016 mg/kg bw/day	0.004	ECETOC TRA worker
Inhalation - Long-term - systemic effects	1.5 mg/m <sup>3</sup>	1.2	ECETOC TRA worker
Sum RCR - Long-term - systemic effects		1.204	

#### 1.3.8. Worker exposure Worker Contributing Scenario (PROC5)

#### Information for contributing exposure scenario

Dermal uptake of solid citrates is expected to be negligible and is not considered, Dermal uptake factor of 0.02 applied for the liquid formulation

Definal uptake of solid citrates is expected to be negligible and is not considered, Definal uptake factor of 0.02 applied for the liquid formulation			
Route of exposure and type of effects	Exposure estimate	RCR	Method
Dermal - Long-term - systemic effects	0.0054 mg/kg bw/day	0.002	ECETOC TRA worker
Inhalation - Long-term - systemic effects	0.5 mg/m <sup>3</sup>	0.4	ECETOC TRA worker
Sum RCR - Long-term - systemic effects		0.402	

#### 1.3.9. Worker exposure Worker Contributing Scenario (PROC8a)

Route of exposure and type of effects	Exposure estimate	RCR	Method
Inhalation - Long-term - systemic effects	1 mg/m³	0.8	ECETOC TRA worker
Sum RCR - Long-term - systemic effects		0.8	

#### 1.3.10. Worker exposure Worker Contributing Scenario (PROC8b)

Route of exposure and type of effects	Exposure estimate	RCR	Method
Inhalation - Long-term - systemic effects	0.5 mg/m³	0.4	ECETOC TRA worker
Sum RCR - Long-term - systemic effects		0.4	

#### 1.3.11. Worker exposure Worker Contributing Scenario (PROC9)

Route of exposure and type of effects	Exposure estimate	RCR	Method
Inhalation - Long-term - systemic effects	0.4 mg/m <sup>3</sup>	0.32	ECETOC TRA worker
Sum RCR - Long-term - systemic effects		0.32	

#### 1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 1.4.1. Environment

Guidance - Environment	No additional risk management measures, besides those that are mentioned above, are needed to guarantee safe use for environment.
Environment Scaling Method	EUSES v 2.1.1

#### 1.4.2. Health

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Guidance - Health	No additional risk management measures, besides those that are mentioned above, are needed to guarantee safe use for workers.
Health Scaling Method	ECETOC TRA worker

#### Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

#### 2. 2: Consumer use

#### 2.1. Title section

Consumer use	ES Ref.: 2	Date of issue: 23/02/2016
	ES Type: Consumer	
	Version: 1.0	

Environment		
	Contributing scenario controlling environmental exposure	ERC8a
Consumer		
	Contributing scenario consumer end-use	PC39

Processes, tasks, activities covered Consumer use

#### 2.2. Conditions of use affecting exposure

#### 2.2.1. Control of environmental exposure: Contributing scenario controlling environmental exposure (ERC8a)

ERC8a Wide dispersive indoor use of processing aids in open systems

#### Product (article) characteristics

Physical form of product	Solid

#### Amount used, frequency and duration of use (or from service life)

Annual amount used in the EU	350 t/yr
Fraction of EU tonnage used in region:	10 %
Fraction of Regional tonnage used locally:	0.0005
Amounts used	0.05 kg/day
	(Zn)
Emission days	365

#### 2.2.2. Control of consumer exposure: Contributing scenario consumer end-use (PC39)

PC39	Cosmetics, personal care products

#### Product (article) characteristics

Physical form of product	Solid

#### 2.3. Exposure estimation and reference to its source

#### 2.3.1. Environmental release and exposure Contributing scenario controlling environmental exposure (ERC8a)

Release route		Release rate			Release estimation method		
Release fraction to air from wide dispersive use (regional only):		0 %					
Release fraction to wastewater from wide dispersive		100 %					
use:							
Protection target	Unit	Exposi		PNEC	RCF	₹	Assessment method

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment method
Freshwater	μg/l	0.175	7.8	0.022	EUSES
Marine water	μg/l	0.0222	2	0.011	EUSES
Freshwater sediment	mg/kg	4.19	11	0.381	EUSES
Marine water sediment	mg/kg	0.531	1.1	0.483	EUSES
Sewage treatment plant	μg/l	24	52	0.462	EUSES
Soil	mg/kg	0.787	23	0.034	EUSES

#### 2.3.2. Consumer exposure Contributing scenario consumer end-use (PC39)

#### Information for contributing exposure scenario

In accordance to the Article 14 (5b) of the REACh Regulation (EC) No 1907/2006, exposure estimation and risk characterisation for human health does not need to be performed for end uses in cosmetic products within the scope of Directive 76/768/EEC

#### 2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 2.4.1. Environment

Guidance - Environment	No additional risk management measures, besides those that are mentioned above, are needed to guarantee safe use for environment.
Environment Scaling Method	EUSES v 2.1.1

#### 2.4.2. Health

Guidance - Health	Consumer use of this product is covered by the conditions of the EU Cosmetics Directive 76/768/EEC and will not be addressed under this review
Health Scaling Method	ECETOC TRA worker

2/11/2019 (Version: 8.1) EN (English) 15/16

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830